

HARLEY-DAVIDSON®

ROAD GLIDE®



HIGHLIGHTS

- **Mechanical Adjustable Actuation Clutch**
- **Limited 3-year, 60,000 Mile Factory Warranty**
 - Police Duty Only
 - Fully transferable
 - Expires after 3 years or 60,000 miles (whichever comes first)

UNIQUE FEATURES

- **121 VVT Engine**
- **New Air Intake**
- **New Cooling System**
- **Increased Lean Angle**
- **New Adjustable Seat**
- **New Factory Installed Chopped Tour-Pak & Mounting Rack**
- **New Charging System**
 - 58 peak amps
- **New Hand Controls**
- **New Factory Installed Siren**
- **New Factory Installed Lights**
- **New Skyline OS Software**
 - Embedded Navigation
 - 12.3 inch TFT display
 - New Infotainment
 - Bluetooth Helmet system with over the Air (OTA) software updates
- **AM & FM Radio/Speakers**
- **Ride Modes**
 - Road, Sport, Rain, and Custom
- **RDRS Rider Safety Enhancements**
 - Cornering Enhanced ABS (C-ABS)
 - Cornering Enhanced Elec. Linked Braking (C-ELB)
 - Cornering Enhanced Trac. Control System (C-TCS)
- **Heated Hand Grips**
- **Pivoting Footboards with Heel/Toe Shift Lever**
- **Reflex™ Linked Premium Brembo® Brakes with ABS**
- **Independent Hazard Warning Switch**
- **Saddlebags**
 - One-Touch latch
 - Standard saddlebag guard and luggage locks
 - Common with ignition key

DIMENSIONS

Length	94.5 in. (2400 mm)
Overall Width	37.8 in. (960 mm)
Overall Height	56.9 in. (1445 mm)
Seat Height	Laden¹ 31.3 in. (795 mm) Unladen 32.3 in. (820 mm)
Ground Clearance	5.6 in. (142 mm)
Rake (Steering Head)	26 degrees
Fork Angle	29.25 degrees
Trail	6.7 in. (170 mm)
Wheelbase	64 in. (1625 mm)
Fuel Capacity	6 gal. (22.7 L)
<i>(Warning light at approx. 1 gal.)</i>	
Weight	
• As Shipped	866 lb. (392 kg.)
• In Running Order	904 lb. (410 kg.)
• Gross Vehicle Weight Rating	1360 lb. (617 kg.)
• Gross Axle Weight Rating	
-Front	500 lb. (227 kg.)
-Rear	927 lb. (420 kg.)

ENGINE

Engine	121 VVT
Valves	• Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; four valves per cylinder
Bore x Stroke	4.075 in. x 4.625 in.
Displacement	121 cu. in. (1982 cc)
Compression Ratio	11.4:1

PERFORMANCE

Engine Torque ² (per J1349):	
• North America	139 ft. lb. @ 3000 RPM (188 Nm @ 3000 RPM)
Lean Angle (per J1168):	
• Right	34 degrees
• Left	33 degrees
Fuel Economy ³	45 mpg
<i>(EPA estimate – combined MPG)</i>	
	(5.2 L/100 km)

CHASSIS

Frame	
• Mild steel; tubular frame; two-piece stamped and welded backbone; cast and forged junctions; twin downtubes; bolt-on rear frame with forged fender supports; MIG welded.	
Swingarm	
• Mild steel, two-piece drawn and welded section, forged junctions, MIG welded	
Front Fork	49 mm Dual Bending Valve
Rear Shocks	
• Premium standard height hand-adjustable rear suspension	
Wheels	Impeller Cast Aluminum
• Front	17 in. x 3 in. (432 mm x 76 mm)
• Rear	16 in. x 5 in. (406 mm x 127 mm)
Brakes	32 mm, 4-piston front & rear
• Rotor type (diameter x width)	
-Front (dual floating rotors)	11.8 in. x 0.2 in.
-Rear (fixed rotor)	11.8 in. x 0.28 in.
• Anti-lock Braking System	Standard
Suspension Travel	
• Front Wheel	4.6 in. (117 mm)
• Rear Wheel	3 in. (76 mm)

1. Measurement reflects 180 lb. (81.7 kg) operator weight.

2. Values shown are nominal.

3. The combined fuel economy numbers were derived using a combination of estimated city and highway values. Fuel economy estimates are derived from US EPA exhaust emission certification data on a sample motorcycle from the corresponding family under ideal laboratory conditions. Your actual fuel economy will vary depending on your personal riding habits, road and driving conditions, vehicle condition and maintenance, tire pressure, vehicle configuration (parts and accessories), and vehicle loading (cargo, rider and passenger weight). Break-in mileage may vary.

Visit [H-D.com/Police](https://www.harley-davidson.com/police) for additional specifications and available color options.